

## XTC 0W20 Syntronic LL

**Bardahl XTC 0W20 Syntronic LL (longlife)** is a fully synthetic engine oil, mandatory for the latest engines from VW/Audi. This oil has been developed to create a clean engine with minimal pollution. Protects against wear, so that the engine remains like new and continues to perform. This lubricating oil has been developed for a maximum service life of emission systems and maximum efficiency. Due to the ultra-low 0W20 viscosity class, a substantial fuel saving is achieved.

### Applications

**Bardahl XTC 0W20 Syntronic LL** has been developed for mandatory use in the new 2.0 TFSI 140 kW and 3.0 TDI CR 160 kW engines from VW and Audi that require VW specifications 508 00 and 509 00.

### Characteristics

- Fuel savings: contributes to fuel savings and reduction of CO2 emissions.
- Good engine protection: performance in terms of keeping the engine clean.
- Cold start: very good fluidity at low temperatures.

### Specifications

ACEA - C5 | ACEA - C6 | API - SN PLUS | API - SP | ILSAC - GF-6 A | FORD - WSS-M2C956-A1 | PORSCHE - C20 | VW - 508 00/509 00 | VW - TL 525 77

### Analytical data

Test			Results
SAE - Class	Method	Unit	XTC 0W20 Syntronic LL
Density 15 °C	ASTM D4052	g/ml	0.835
CCS-viscosity at -35 °C,	ASTM D5293	mPa.s	3500
Viscosity at 40 °C	ASTM D445	mm <sup>2</sup> /s	40.2
Viscosity at 100 °C	ASTM D445	mm <sup>2</sup> /s	8.2
Viscosity index	ASTM D2270		184
Flashpoint COC, °C	ASTM D92	°C	235
Pour point, °C	ASTM D6892	°C	-51
Total Base Number	ASTM D2896	mg KOH/g	8.3
Sulfated Ash; wt.%	ASTM D874	wt.%	0.79
Color	VISUAL		Green

**Article number** 54851  
**Contents** 1 liter

**Article number** 54855  
**Contents** 5 litres

**Article number** 54882  
**Contents** 25 litres



## PRODUCT INFORMATION

**Article number** 54886

**Contents** 60 litres

**Article number** 54892

**Contents** 210 litres