

NAUTIC MOTOR OIL 15W30

Bardahl NAUTIC Motor Oil 15W30 is an engine oil that has been specially developed for modern and (very) fast 4-stroke inboard engines for both petrol and diesel engines with or without turbo. The extensive package of additives, in combination with the best base oil, ensures maximum protection against friction and wear and prevents the formation of black sludge. This engine oil enables long drain intervals and the friction-reducing additives ensure lower fuel consumption.

Application

Suitable for very powerful (high revs and loads) 4-stroke inboard engines for both petrol and diesel engines with or without turbo. Recommended for faster pleasure craft that needs to deliver high performance.

Specifications

API Service SL/CI-4/CH-4/CG-4 | MAN : 271 | MTU : Type 2 | Volvo : VDS2/ VDS3 | Cummins: CES20076-77/20078 | Deutz: DQC0305 | Caterpillar: ECF-1A

Analysis data

Test			Results
SAE - Klasse	Method	Unit	MOTOR OIL 15W30
Dichtheid bij 15 °C	ASTM D4052	g/ml	0.886
Viscositeit 40 °C	ASTM D445	mm ² /s	108
Viscositeit 100 °C	ASTM D445	mm ² /s	14.5
Viscositeitindex	ASTM D2270		136
Vlampunt COC	ASTM D92	°C	220
Pour point		°C	-27
Total Base Number	ASTM D2896	mg KOH/g	10.4
Sulfate ash	ASTM D874	Wt %	1.49

Article number 48151

Content 1 liter

Article number 48155

Content 5 liter

Article number 48182

Content 25 liter

Article number 48186

Content 60 liter

Article number 48192

Content 210 liter