

XTC LA 5W30 Syntronic

Bardahl LA 5W30 Syntronic is a fuel-saving, universal engine oil, developed according to the latest techniques, based on specially selected base oils, to which advanced additives have been added to obtain the following properties:

Property

- Fuel savings
- Reduced formation of combustion residues (mid SAPS)
- A smooth cold start
- A safe lubricating film at high operating temperatures
- Extended drain intervals
- A very good deterging and dispersing effect
- A very strong anti-wear, anti-corrosion and antifoaming ability

Application

Bardahl LA 5W30 Syntronic is a universal, fuel-saving, specially formulated engine oil, suitable for petrol, LPG and diesel engines, both without and with turbocharging, in passenger and vans, for which extended drain intervals are possible.

This engine oil also contributes to the extension of the service life of diesel particulate filters, due to the low SAPS content. Due to its special composition, this product can be used excellently for MB 229.31 and BMW Longlife 04.

*Extra : Meets all engine protection requirements of ACEA C2.

Specifications

ACEA - C2 | ACEA - C3 | BMW - LONGLIFE-04 | FIAT - 9.55535-S1 | FIAT - 9.55535-S3 | FORD - WSS-M2C917-A | GM - DEXOS2™ | HYUNDAI - . | IVECO - 18-1811 CLASSE SC1 | KIA - . | MB - 226.52 | MB - 229.31 | MB - 229.51 | MB - 229.52 | OPEL - GM-LL-A-025 | OPEL - GM-LL-B-025 | OPEL - OV 040 1547 - D30 | RENAULT - RN17 LEVEL | VW - 505 00 | VW - 505 01

Analysis data

SAE - Class	Test		Results
	Method	Unit	LA 5W30 Syntronic
Density , kg/l15 °C	ASTM D4052	g/ml	0,852
Viscosity , m Pa. s-30 °C		m Pa. s	5970
Viscosity , mm ² /s40 °C	ASTM D445	mm ² /s	76
Viscosity , mm ² /s100 °C	ASTM D445	mm ² /s	12,20
Viscosity index	ASTM D2270		169
Pour point, °C	ASTM D6892	°C	-33
Total Base Number, mg KOH/g	ASTM D2896	mg KOH/g	8,1
Flash point °C	ASTM D92	°C	>240



Article number 50351
Contents 1 liters

Article number 50355
Contents 5 liters

Article number 50382
Contents 25 liters

Article number 50386
Contents 60 liters

Article number 50392
Contents 210 liters