

XTC FS 5W30 Synthetic

A modern economical universal motor oil with special base oils give it the natural high viscosity index. With an extensive package of additives, the following properties are achieved:

Properties

- Increases fuel economy
- The high viscosity index protects the motor from temperature influences
- Improved cold start
- A safe lubricating film at high operating temperatures
- Excellent cleaning properties
- Provides high protection against wear, corrosion and antifoam

Application

A universal motor oil that is suitable for use in all motors, where a 5W30 A1/B1 A5/B5 is prescribed.

Specifications

ACEA - A1/B1-12 | ACEA - A5/B5 | API - CF | API - SL | ILSAC - GF-5 | FIAT - 9.55535-G1 | FORD - WSS-M2C913-C/D | JAGUAR-LAND ROVER - STJLR.03.5003 | RENAULT - RN 0700 | VW - 530 36

Analysis data

Test			Results
SAE - Class	Method	Unit	fs 5w30
Density 15 °C	ASTM D4052	g/ml	0,863
Viscosity; m Pa. s at -30 °C	ASTM D5293	mPa.s	6400
Viscosity; mm ² /s at 40 °C	ASTM D445	mm ² /s	67,40
Viscosity; mm ² /s at 100 °C	ASTM D445	mm ² /s	10,90
Viscosity index	ASTM D2270		153
Flashpoint COC, °C	ASTM D92	°C	220
Pour point, °C	ASTM D6892	°C	-40
Total Base Number	ASTM D2896	mg KOH/g	9,7
Sulfated Ash; wt. %	ASTM D874	wt. %	1,12

Article number 50851
Contents 1 liter

Article number 50855
Contents 5 liter

Article number 50882

Contents 25 litres

Article number 50886
Contents 60 litres

Article number 50892
Contents 210 litres