



Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 08/09/2014 Revision date: 05/04/2022 Supersedes version of: 31/08/2020 Version: 2.6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : Spray Paint Black
UFI : D360-H0FK-500X-NTCJ
Product code : 648
Article number : 64804

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Consumer use
Industrial use
Professional use.
Function or use category : Paint.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BARDAHL NL - OCD NEDERLAND BV
Maxwellstraat 41
3316 GP Dordrecht
Nederland
T 0031 78 651 2322 - F 0031 78 617 4848
mjkooijman@bardahl.nl - www.bardahl.nl

1.4. Emergency telephone number

Emergency number : +31 (0) 6 54924171
During office hours: 8.30 t/m 17:00 h

Country	Official advisory body	Address	Emergency number	Comment
	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Spray Paint Black


Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

EUH-statements

- : Danger
- : ACETONE
- : H222 - Extremely flammable aerosol.
- H229 - Pressurised container: May burst if heated.
- H319 - Causes serious eye irritation.
- H336 - May cause drowsiness or dizziness.
- : P102 - Keep out of reach of children.
- P261 - Avoid breathing vapours, spray.
- P271 - Use only outdoors or in a well-ventilated area.
- P280 - Wear eye protection/face protection, protective clothing, protective gloves.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 - If eye irritation persists: Get medical advice/attention.
- P501 - Dispose of contents and container to in accordance with local regulations..
- P210 - Keep away from heat, hot surfaces, open flames, sparks. – No smoking.
- P211 - Do not spray on an open flame or other ignition source.
- P251 - Pressurized container: Do not pierce or burn, even after use.
- P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- : EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

PBT: not relevant – no registration required

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ACETONE	CAS-No.: 67-64-1 EC-No.: 200-662-2 REACH-no: 01-2119471330-49	30 – 60	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
xylene (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	5 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methoxy-1-methylethyl acetate	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	1 – 5	Flam. Liq. 3, H226
ethylbenzene	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	1 – 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Solvent naphtha (petroleum), light aromatic	CAS-No.: 64742-95-6 EC-No.: 265-199-0 EC Index-No.: 649-356-00-4 REACH-no: 01-2119486773-24	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-butoxyethanol; ethylene glycol monobutyl ether	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108-36	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (Note D)	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6	≥ 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In any case of doubt or if symptoms can be observed, get medical attention. If possible, show the doctor this safety data sheet. Failing this, show the doctor the packaging or label. First aider: Pay attention to self-protection!.
First-aid measures after inhalation	: Keep the victim warm. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or a doctor if you feel unwell. When unconsciousness transport in a recovery position.
First-aid measures after skin contact	: Wash skin thoroughly with mild soap and water.
First-aid measures after eye contact	: Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting, unless told so by a poison control center or doctor. In any case of doubt or if symptoms can be observed, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: The severity of the symptoms described will vary depending on the concentration and the duration of exposure.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Symptoms/effects after eye contact : May cause irritation to the eyes.
Symptoms/effects after ingestion : Ingestion unlikely.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water haze. Powder. Carbon dioxide. Alcohol resistant foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Explosion hazard : Explosion risk in case of fire. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. May form flammable/explosive vapour-air mixture.
Hazardous decomposition products in case of fire : Carbon monoxide. Carbon dioxide.

5.3. Advice for firefighters

Precautionary measures fire : Do not breathe smoke. Evacuate area.
Firefighting instructions : Use water spray or fog for cooling exposed containers. Remove container to open air and flood with water. Prevent fire fighting water from entering the environment. Use water spray to disperse the vapours.
Protection during firefighting : Positive pressure self-contained breathing apparatus (SCBA) and structural fire-fighters protective clothing. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.
Other information : Notify authorities if product enters sewers or public waters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. Ventilate area. No open flames. No smoking. No flames, no sparks. Eliminate all sources of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters. Small amounts: No significant hazards.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean contaminated surface thoroughly. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take up liquid spill into absorbent material. Contain and dispose of waste according to local regulations.
Other information : Ventilate area.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". More detailed information: See section 11. Ecological information (Section 12). For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Good ventilation of the workplace required.
Precautions for safe handling	: Avoid contact with skin and eyes. Wear suitable protective clothing. This product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not expose to temperatures exceeding 50 °C/ 122 °F. Do not breathe gas, fumes, vapour or spray.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a dry, cool and well-ventilated place.
Incompatible materials	: heat. sparks. Open flame. Direct sunlight.
Storage area	: Chemical storage.
Special rules on packaging	: Opened containers must be carefully closed and kept upright to avoid leakage.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	221 mg/m ³ (Xylene, mixed isomers, pure; EU; Timeweighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	50 ppm (Xylene, mixed isomers, pure; EU; Timeweighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	442 mg/m ³ (Xylene, mixed isomers, pure; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	100 ppm (Xylene, mixed isomers, pure; EU; Short time value; Indicative occupational exposure limit value)
ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	442 mg/m ³ (Ethylbenzene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	100 ppm (Ethylbenzene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	884 mg/m ³ (Ethylbenzene; EU; Short time value; Indicative occupational exposure limit value)

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
IOEL STEL [ppm]	200 ppm (Ethylbenzene; EU; Short time value; Indicative occupational exposure limit value)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	441 mg/m ³ Ethylbenzene; United Kingdom; Timeweighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL TWA (OEL TWA) [2]	100 ppm Ethylbenzene; United Kingdom; Timeweighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL)	552 mg/m ³ Ethylbenzene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL) [ppm]	125 ppm Ethylbenzene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective goggles.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection			
Type	Field of application	Characteristics	Standard
tightly fitting safety goggles			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. EN 13034

Hand protection:

Refer to manufacturer's information.

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Safety gloves					EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection

Device	Filter type	Condition	Standard
Self-contained breathing apparatus (SCBA)			EN 14387, EN 136, EN 140

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing immediately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not breathe gas, fumes, vapour or spray. Avoid contact with skin and eyes.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Black.
Odour	: organic solvent.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: -40 – -2 °C LPG
Flash point	: -104 °C LPG
Auto-ignition temperature	: 365 °C LPG
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 590 – 1760 kPa LPG
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1.4 – 10.9 vol % (V) LPG

9.2. Other information

Volatility	: Volatile
------------	------------

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Oxidising agents.

10.4. Conditions to avoid

Heat. Open flame. Sources of ignition. Freezing. Direct sunlight. High temperature.

10.5. Incompatible materials

None under normal conditions.

10.6. Hazardous decomposition products

No hazardous decomposition products known. Thermal decomposition generates : hazardous gases. Vapours.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

xylene (1330-20-7)

LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 Inhalation - Rat	6350 mg/l/4h

ethylbenzene (100-41-4)

LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15415 mg/kg
LC50 Inhalation - Rat	17.8 mg/l/4h
LC50 Inhalation - Rat [ppm]	4000 ppm/4h

Solvent naphtha (petroleum), light aromatic (64742-95-6)

LD50 oral rat	3295 mg/kg
LD50 dermal rat	> 3160 mg/kg
LC50 Inhalation - Rat (Vapours)	> 10.2 mg/l/4h

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)

LD50 oral rat	1480 mg/kg
LD50 dermal rabbit	400 mg/kg

Skin corrosion/irritation : Prolonged or repeated contact may cause skin to become dry or cracked.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause respiratory irritation. High concentrations may cause headache, dizziness, nausea, dullness and other effects on the central nervous system that lead to vision impairment, respiratory disorders and convulsions.

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

ACETONE (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Solvent naphtha (petroleum), light aromatic (64742-95-6)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

ethylbenzene (100-41-4)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard	: Not classified
Additional information	: Ingestion unlikely Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause chemical burns in mouth, oesophagus and stomach.. May cause discomfort if swallowed. May cause stomach pain or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

xylene (1330-20-7)

LC50 - Other aquatic organisms [1]	8.9 – 16.4 mg/l (Pimephales promelas 96h)
EC50 - Crustacea [1]	3.2 – 9.5 mg/l (Daphnia magna) (48h)

ethylbenzene (100-41-4)

LC50 - Fish [2]	4.2 mg/l
-----------------	----------

Solvent naphtha (petroleum), light aromatic (64742-95-6)

LC50 - Other aquatic organisms [2]	9.2 mg/l (Oncorhynchus mykiss (96h))
EC50 - Crustacea [1]	3.2 mg/l (48h)
NOEC (acute)	1 mg/l (Pseudokirchneriella subcapitata) (72h)

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)

LC50 - Fish [1]	1490 mg/l
EC50 - Crustacea [1]	1815 mg/l
EC50 72h - Algae [1]	1490 mg/l
EC50 72h - Algae [2]	911 mg/l

12.2. Persistence and degradability

Spray Paint Black

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

xylene (1330-20-7)	
Persistence and degradability	Readily biodegradable.
ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 % ThOD
2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
Biodegradation	96 %
12.3. Bioaccumulative potential	
Spray Paint Black	
Bioaccumulative potential	Bioaccumulation unlikely.
xylene (1330-20-7)	
BCF - Fish [2]	7 – 26
Bioconcentration factor (BCF REACH)	< 500
Partition coefficient n-octanol/water (Log Pow)	3.2
ethylbenzene (100-41-4)	
BCF - Fish [1]	1
BCF - Fish [2]	15 – 79
BCF - Other aquatic organisms [1]	4.68
Bioconcentration factor (BCF REACH)	< 500
Partition coefficient n-octanol/water (Log Pow)	3.15
2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.83
Bioaccumulative potential	Low.
12.4. Mobility in soil	
Spray Paint Black	
Ecology - soil	The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.
xylene (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
ethylbenzene (100-41-4)	
Surface tension	0.029 N/m
Organic Carbon Normalized Adsorption Coefficient (Log K _{oc})	PCKOCWIN v1.66; 2.71; Calculated value; K _{oc} ; PCKOCWIN v1.66; 517.8; Calculated value
2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
Surface tension	2.729 N/m

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	8
--	---

12.5. Results of PBT and vPvB assessment

Spray Paint Black

PBT: not relevant – no registration required

12.6. Other adverse effects

Other adverse effects : The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not empty into drains.

SECTION 14: Transport information

In accordance with / / ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No

SECTION 16: Other information

Indication of changes

Section	Changed item	Change	Comments
	Volatility	Added	
	Segregation (IMDG)	Added	
	Stowage and handling (IMDG)	Added	

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Indication of changes			
Section	Changed item	Change	Comments
	Special provisions for carriage - Operation (ADR)	Added	
	Special provisions for carriage - Loading, unloading and handling (ADR)	Added	
	Special provisions for carriage - Packages (ADR)	Added	
	Mixed packing provisions (ADR)	Added	
	Special packing provisions (ADR)	Added	
	Packing instructions (ADR)	Added	
	Transport category (RID)	Added	
	Special provisions (RID)	Added	
	Special packing provisions (RID)	Added	
	Special provisions for carriage – Packages (RID)	Added	
	Special provisions for carriage - Loading, unloading and handling (RID)	Added	
	Packing instructions (RID)	Added	
	Mixed packing provisions (RID)	Added	
	Limited quantities (RID)	Added	
	Hazard identification number (RID)	Added	
	Excepted quantities (RID)	Added	
	Colis express (express parcels) (RID)	Added	
	Classification code (RID)	Added	
	Ventilation (ADN)	Added	
	Limited quantities (ADN)	Added	
	Danger labels (ADN)	Added	
	Excepted quantities (ADN)	Added	
	Equipment required (ADN)	Added	
	Classification code (ADN)	Added	
	Number of blue cones/lights (ADN)	Added	
	Stowage category (IMDG)	Added	
	Special provisions (IMDG)	Added	
	EmS-No. (Spillage)	Added	
	EmS-No. (Fire)	Added	
	Special provisions (IATA)	Added	
	PCA packing instructions (IATA)	Added	
	PCA max net quantity (IATA)	Added	
	PCA limited quantity max net quantity (IATA)	Added	
	PCA Limited quantities (IATA)	Added	
	PCA Excepted quantities (IATA)	Added	

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Indication of changes			
Section	Changed item	Change	Comments
	ERG code (IATA)	Added	
	CAO packing instructions (IATA)	Added	
	CAO max net quantity (IATA)	Added	
	Irritation - comment	Added	
	Skin corrosion/irritation - comment	Added	
	Respiratory or skin sensitisation - comment	Added	
	Danger labels (IMDG)	Added	
	Danger labels (IATA)	Added	
	SDS EU format	Added	
	UN-No. (RID)	Added	
1.2	Industrial/Professional use spec	Added	
1.2	Function or use category	Added	
2.1	Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]	Added	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Added	
2.2	EUH-statements	Added	
2.2	Precautionary statements (CLP)	Added	
2.2	Signal word (CLP)	Added	
2.2	Hazard statements (CLP)	Added	
2.2	Hazard pictograms (CLP)	Added	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures general	Added	
4.1	First-aid measures after skin contact	Added	
4.1	First-aid measures after inhalation	Added	
4.1	First-aid measures after ingestion	Added	
4.1	First-aid measures after eye contact	Added	
4.2	Symptoms/effects after skin contact	Added	
4.2	Symptoms/effects after inhalation	Added	
4.2	Symptoms/effects after ingestion	Added	
4.2	Symptoms/effects after eye contact	Added	
4.2	Symptoms/effects	Added	
4.3	Other medical advice or treatment	Added	
5.1	Unsuitable extinguishing media	Added	
5.1	Suitable extinguishing media	Added	
5.2	Hazardous decomposition products in case of fire	Added	
5.2	Explosion hazard	Added	
5.3	Precautionary measures fire	Added	

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Indication of changes			
Section	Changed item	Change	Comments
5.3	Protection during firefighting	Added	
5.3	Firefighting instructions	Added	
5.3	Other information	Added	
6.1	General measures	Added	
6.2	Environmental precautions	Added	
6.3	Methods for cleaning up	Added	
6.3	Other information	Added	
6.4	Reference to other sections (8, 13)	Added	
7.1	Additional hazards when processed	Added	
7.1	Precautions for safe handling	Added	
7.1	Hygiene measures	Added	
7.2	Incompatible materials	Added	
7.2	Storage conditions	Added	
7.2	Storage area	Added	
7.2	Special rules on packaging	Added	
8.2	Other information	Added	
8.2	Personal protective equipment	Added	
8.2	Hand protection	Added	
8.2	Skin and body protection	Added	
9.1	Colour	Added	
9.1	Vapour pressure	Added	
9.1	Odour	Added	
9.1	Flash point	Added	
9.1	Explosive limits (vol %)	Added	
9.1	Boiling point	Added	
9.1	Auto-ignition temperature	Added	
9.1	Appearance	Added	
10.2	Chemical stability	Added	
10.3	Possibility of hazardous reactions	Added	
10.4	Conditions to avoid	Added	
10.5	Incompatible materials	Added	
10.6	Hazardous decomposition products	Added	
11.1	Additional information	Added	
12.2	Persistence and degradability	Added	
12.3	Bioaccumulative potential	Added	
12.4	Ecology - soil	Added	
12.6	Other adverse effects	Added	
13.1	Waste disposal recommendations	Added	

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Indication of changes			
Section	Changed item	Change	Comments
14.1	UN-No. (ADN)	Added	
14.1	UN-No. (ADR)	Added	
14.1	UN-No. (IMDG)	Added	
14.1	UN-No. (IATA)	Added	
14.3	Danger labels (ADR)	Added	
14.3	Class (ADR)	Added	
14.3	Danger labels (RID)	Added	
14.6	Special provisions (ADN)	Added	
14.6	Special packing provisions (IMDG)	Added	
14.6	Packing instructions (IMDG)	Added	
14.6	Classification code (ADR)	Added	
14.6	Transport category (ADR)	Added	
14.6	Special provisions (ADR)	Added	
14.6	Limited quantities (ADR)	Added	
14.6	Excepted quantities (ADR)	Added	
14.6	Tunnel restriction code (ADR)	Added	
15.2	Chemical safety assessment	Added	
16	Abbreviations and acronyms	Added	

Abbreviations and acronyms:	
	<p>Abbreviations and acronyms:</p> <p>RID: Regulations Concerning the International Transport of Dangerous Goods by Rail ICAO: International Civil Aviation Organization ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent</p>

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

Spray Paint Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.